

Product data sheet

Specifications



SCHUKO sock.-out. w. hng.lid, IP44, shut., screwl. term., anthracite, System M

MTN2314-0414

Main

| | |
|--------------------------------------|--|
| Aesthetic name | System M M-Smart M-Elegance M-Plan M-Arc M-Star M-Plan glass |
| Product or component type | Socket-outlet |
| Device presentation | Mechanism with central plate |
| Outlet standard | German |
| Socket additional information | With hinged lid |

Complementary

| | |
|---------------------------------------|-----------------------|
| Outlet poles configuration | 2P + E |
| Wiring device mounting | Flush |
| Fixing mode | By screws and claws |
| Rated current | 16 A |
| [Ue] rated operational voltage | 250 V |
| Colour tint | Anthracite (RAL 7024) |
| Connections - terminals | Screwless terminals |
| Material | Polycarbonate matt |

Environment

| | |
|--------------------------------|------|
| IP degree of protection | IP44 |
|--------------------------------|------|

Packing Units

| | |
|-------------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 102 g |
| Package 1 Height | 5.3 cm |
| Package 1 width | 7.6 cm |
| Package 1 Length | 7.6 cm |
| Unit Type of Package 2 | CAR |

| | |
|-------------------------------------|---------|
| Number of Units in Package 2 | 50 |
| Package 2 Weight | 5.51 kg |
| Package 2 Height | 18.5 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|--------------------------|---|
| EU RoHS Directive | Under investigation |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|
