

Product data sheet

Specifications



Sedna Design & Elements, 2-circuits switch 10AX, professional, aluminium

SDD213105

Main

Range	Sedna
Product or component type	Switch
Device presentation	Mechanism with fixing frame
Device application	Control
Switch function	2-circuits

Complementary

Device mounting	Flush
Load type	1 lamp integrated ballast (100 W)
Surface finish	Painted
Kind of terminals	Screwless terminals
Accessory / separate part type	Claw and screw for mechanism
Power range	2300 W
Cable cross section	2.5 mm²
Wire structure	Rigid
Wire stripping length	13 mm
Fixing mode	Claws, span of claws working range: 51...70 mm Claws, span of claws working range: 52...68 mm Screws
Height	73 mm
Width	73 mm
Depth	38 mm
Depth of visual part	24 mm
Net weight	0.070 kg
Targeted channel	Professional

Environment

IP degree of protection	IP44
Conformity mark	CE
Product certifications	GOST-R

Standards	IEC 60669-1
-----------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	75.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	18.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	832.0 g
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	40.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	10.631 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)