

Technique for cable laying and overhead line construction



- Energy cable laying up to 680 kV
- Fibre optic, mini and micro cables
- Cable winding and length measuring
- Overhead line construction up to 110 kV
- Seminars and product instructions

Cable supporting grips, 1 loop, stainless steel



Cable supporting grips with 1 loop. Stainless steel Bowden wire V4A/1.4401 with copper clamp. All Vetter cable grips are handmade therefore of high flexibility. They adapt easy at any difference in cable diameter and are therefore simple to handle. Other versions, e.g. reinforced, different length are available. For safe and strain relieved cable supporting.

- L1 = the lengths without cables in. L2 = total length included the loops.
- The real length mounted on the cable can be much shorter, depending on the cable diameter.
- Loops without thimbles
- B = internal diameter of the loop
- D = thickness of the loop
- kN = minimum breaking load

Code	Type	C-D	B	D	kN	L1/L2	kg
250271	KME 6/1	4-6	30	2	1,8	100/275	0,02
250281	KME 9/1	7-9	30	2	3,3	120/290	0,02
250291	KME 12/1	9-12	30	2	3,9	135/340	0,02
250321	KME 15/1	12-15	30	2	6,3	180/390	0,02
250341	KME 19/1	15-19	30	3	7,8	220/450	0,04
250371	KME 25/1	19-25	35	3	7,8	275/510	0,05
250411	KME 30/1	25-30	35	3	12,0	350/610	0,07
250421	KME 40/1	30-40	50	3	17,4	370/660	0,12
250441	KME 50/1	40-50	50	4	24,0	490/800	0,12
250451	KME 60/1	50-60	50	4	24,0	500/810	0,28
250461	KME 70/1	60-70	50	5	31,8	520/860	0,28

Vetter GmbH Kabelverlegetechnik • Industriestraße 28 • D-79807 Lottstetten

Tel.: +49 7745/9293-0 • Fax +49 7745/9293-499 • info@vetter-kabel.de • www.vetter-kabel.de