



# Ledinaire Waterproof Tube Housing

## WT050C 1xTLED L1200

Ledinaire Waterproof Tube Housing, L1200 mm, IP65, IK08

The Ledinaire waterproof (WT050C) range contains a selection of empty, waterproof housings, that can cater for LED tubes of your choice. It comes with the high Philips quality levels at a competitive price. Ledinaire enables, simple and quick installation, with a choice of single and double tube installations.

### Product data

General Information	
Angle	-
Accessory color	Gray
Value ladder	Value

  

Light Technical	
Color rendering index (CRI)	-
Luminaire light beam spread	-

  

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz

  

Mechanical and Housing	
Overall length	1,280 mm
Overall width	69 mm
Overall height	70 mm
Dimensions (Height x Width x Depth)	70 x 69 x 1280 mm

Material	Polycarbonate
----------	---------------

  

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class II
CE mark	CE mark

  

Product Data	
Order product name	WT050C 1xTLED L1200
Full product name	WT050C 1xTLED L1200
Full product code	871016336602999
Order code	911401807381
Material Nr. (12NC)	911401807381
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.700 kg
EAN/UPC - Product/Case	8710163366029
Numerator - Packs per outer box	12

# Ledinaire Waterproof Tube Housing

EAN/UPC - Case

8710163366180

## Dimensional drawing

WT050C L1200 1 Tube

