

ENSTO

Gnybtas izoliuotas/plikas

SEW20.7

Tipas	SEW20.7
GTIN	6438100310493
Pavadinimas	Gnybtas izoliuotas/plikas OLA AI (35)50-157 / OL AI 35-157 mm ²
Aprašymas	Skirtas sujungti vidutinės itampos OLA su OL. Gnybtas pagamintas iš korozijai atsparaus aliuminio lydinio, varžtai iš karštai galvanizuoto plieno. Dantytas gnybto griovelis yra nušveistas ir hermetizuotas silikonine apsaugine pasta.

Gamintojas



Techninė specifikacija

Certificates

Standartinis žymėjimas: EN 50397-2

Dimensions

Pagrindinis laidininkas mm²: Bare 35-157 mm²

Atšakos laidininkas mm²: CC 50-157 mm²

Net Weight: 0,25 kg

Features

Varžtas: 2xM10

Mechanical

Užveržimo momentas: 40 Nm

Others

ETIM Class: EC001062

ETIM Techninė specifikacija

etim

Nominal cross section main conductor SM:	35 ... 157 mm ²
Nominal cross section branch conductor SE/RE:	50 ... 157 mm ²
Nominal cross section branch conductor SM/RM:	50 ... 157 mm ²
Material main conductor:	Aluminium
Material branch conductor:	Aluminium
Terminal insulated:	No
Clamping channel opening main conductor:	Both sides open
Clamping channel opening branch conductor:	Both sides open
Surface protection:	Bare
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	pcs
Package size:	1750
Depth:	1200 mm
Width:	800 mm
Height:	870 mm

Default package

Unit:	pcs
Package size:	25
Depth:	220 mm
Width:	220 mm
Height:	175 mm
Weight:	6,25 kg
Volume:	8,47 l